

# The NASA QBed: A Prototype Differentiated Services Network

#### George Uhl

Raytheon Information Technology and Scientific Services

9 February 2000





# Outline



- Introduction
- Testbed Infrastructure
- Activities
- Summary





#### Introduction



- NASA serves international scientific research community
  - Close working relationships with NASA
    - EOS Instrument team members receive QA data from instruments on-board spacecraft
  - Science community requires data sets
    - NASA generated EOS science data sets open and available to public
- Most scientists located in academic and government institutions
  - Many served by advanced networks
    - vBNS, Abilene, ATDnet





#### Introduction




- NREN is a member of Internet2
- NASA's Earth Observing System (EOS) a major NASA network user
  - Daily movement of several terabytes of data
- NREN partnering with ESDIS in prototyping QoS





#### Introduction



- NASA QBed prototypes emerging QoS network technologies
  - Deploy QoS technologies
  - Demonstrate operational capabilities
  - Test high-end applications
  - Facilitate deployment of new technologies into operations networks








- ESDIS Network Prototyping Lab (ENPL) QBed site a heterogeneous network
  - Mostly Intel-based PCs running FreeBSD with ALTQ queuing subsystem
    - ALTQ developed by Kenjiro Cho of Sony-Japan.
      - www.csl.sony.co.jp/person/kjc/programs.html
  - Two Cisco 7507 routers
  - Cisco 6500 series switch this year
  - FORE ASX-1000 ATM switch
  - Cisco FE, GE switches






















- DiffServ-enabled backbone
  - OC-3 ATM as layer 2 service
  - Traffic conditioned at boundaries
  - Best effort, EF and AF PHBs
- Stub LANs along boundaries
  - Stub LAN serviced by PC router running ALTQ CBQ to optionally pre-condition traffic prior to entry into DiffServ backbone







#### Data generation tools

- Unicast
  - ttcp
  - netperf
  - gen\_send/ gen\_receive
  - Chariot
- Multicast
  - mgen
  - Chariot







- Performance measurement tools
  - Host-based tools measure microflow performance
    - mgen , tdg, netperf`ttcp
      - throughput, rtt, delay, packet loss, jitter
  - Router-based tools monitor DiffServ performance
    - ttt, ALTQ and ENPL ttt derivatives; MRTG
      - monitor traffic conditioner and PHB performance
    - ttt and NeTraMet measure throughput
  - Need DiffServ monitoring/diagnostic tools for Cisco devices







- Current applications being tested
  - Audio/Video
    - vic/vat for multicast
      - Multicast NASA TV feed, peak to 5 Mbps
    - NREN's VCC to be installed
      - Peak to 30 Mbps
  - Multicast
    - mgen to emulate satellite telemetry streams
  - High-rate Data Transfer
    - ftp, ttcp, netperf, peak to near OC-3 line speed







- Capabilities Demonstration
  - Preferred traffic
    - Video and Audio multicast
      - Transmitted between 3 5 Mbps
    - High-rate TCP stream
      - Transmitted at 55 Mbps
  - Congesting traffic
    - High-rate UDP traffic at
      - Transmitted at 40 Mbps







- Capabilities Demonstration
  - Performance Measurements
    - Taken at all router interfaces
    - Traffic conditioning
      - boundary router ingress interface
    - PHB performance in interior
      - boundary router and interior router egress interface
  - Graphs show performance
    - MRTG over long periods
      - data capture at 5-minute intervals
    - ttt derivatives over 5-minute windows
      - data capture at 1-second intervals







#### Capabilities Demonstration

- Configuration
  - Premium service for Video/Audio Multicast
    - Traffic conditioning uses token bucket meter
    - Service built on EF PHBs using CBQ
  - Preferred service for TCP traffic
    - Traffic conditioning uses 2-rate, 3-color marker
    - Service built on AF PHB using CBQ/RIO
  - Best Effort
    - Traffic conditioning uses token bucket meter
    - Best Effort forwarding uses CBQ to limit traffic








- Capabilities Demonstration
  - ATM PVC Configuration
    - ENPL routers equipped with OC-3 ATM NICs
      - With IP, effective throughput at 128 Mbps over backbone
      - Each end of the PVC polices traffic at 64 Mbps
  - Fast Ethernet on LANs







Capabilities Demonstration






Traffic Conditioning on Ingress Interface of Boundary Router





#### Capabilities Demonstration






CBQ Performance Over Egress Interface Of A DiffServ Interior Router







#### Capabilities Demonstration

#### Example MRTG graphs



Traffic Conditioning: Marked/Passed Packets (green) vs. Dropped Packets (blue)











- Evaluating NTP performance over DiffServ
  - Mitigating impact of delay and jitter
- IP to ATM Class of Service Mapping
  - Uses ATM bundles
  - Map IP-based reserved flows to VBR/UBR
  - No noticeable performance hits
  - Bandwidth values consistent with normal sub-interfaces
  - Latency values consistent with normal sub-interfaces
  - Cisco IOS 12.0(5)XE and above (or a 12.05T and above branch)
- CAIRN Network Service Provider to UCL
  - Traffic mostly video teleconferencing







## Spacecraft Clock and Data

- In summer 2000 ESDIS will test sending "Level One" (raw) space data over wide area TCP/IP
- Will use several research networks to send 50-70 Mb/sec.
- Will use DiffServ code point set in the application to insure service levels across domains







- Principal NASA partners
  - NREN at Ames Research Center (ARC)
  - ENPL at Goddard Space Flight Center (GSFC)
    - Also HECN and NILE labs
- External partners
  - Broadband and Wireless Networking Laboratory at Georgia Tech
  - University College London (UCL)








- Future Activities
  - Expansion of the QBed
    - peer with Abilene at ARC and GSFC
  - Enable Cisco DiffServ QoS
  - Prototyping Bandwidth Brokers
  - End-to-end QoS
    - RSVP
  - Prototyping MPLS
    - Integrate with DiffServ
  - NGI applications testing





# Summary



- NASA QBed prototypes emerging QoS technologies
- Prototype QoS solutions for NGI applications and high-end NASA network requirements
- Facilitate deployment of advanced technologies to operational networks
- Web pages
  - http://corn.eos.nasa.gov
  - http://www.nren.nasa.gov/eng/qos.html
  - http://www.ece.gatech.edu/research/labs/bwn
  - http://everest.gsfc.nasa.gov
  - http://nileweb.gsfc.nasa.gov
  - http://www-mice.cs.ucl.ac.uk/multimedia



